

GF22 I

2x2" point source speaker - passive



GF22 is the ultra-compact full-range point source column speaker from GF family. Featuring 2x2" driver units, this speaker delivers exceptional audio quality, particularly in the bass range, thanks to its built-in bass reflex technology.

GF22 is equipped with an Euroblock connector that features 2 additional pins for speaker relaunch, making it effortless to connect GF22I to other speakers in "daisy chain".

This not only simplifies the integration process but also provides flexibility in expanding any audio setup.

With GF22, expecting precise and focused reproduction in a compact and powerful design, along with the added convenience of easy connectivity.

GF22I comes in black (GF22I) and GF2W - white.

Technical specifications

Type	Passive point source loudspeaker
Transducer	2 x 2" ferrite magnet woofer
Frequency Response ¹	90 Hz - 20 kHz (-6dB) ¹
Max SPL ²	108 dB Peak ²
Power Handling	50 W
Coverage	V.90 H.90°
Connectors	4PIN Euroblock with speaker relaunch, Phoenix 1,5/4-ST-3,81 compatible
Nominal Impedance	16 Ω
IP Rating	IP54


Handling & Finishes

Dimensions (WxLxH)	60 x 590 x 72 mm (2.36 x 23.22 x 2.83 in)
Weight	1,3 kg (2.87 lb)
Material	ABS
Color	Black - White (GF22W)

¹ With dedicated preset

² Maximum SPL is calculated using a signal with crest factor 4 (12 dB) measured at 8 m then scaled at 1 m

Example of configuration





Connector and Impedance setting

MC 1,5/ 4-ST-3,81



16Ω Low-Z



Mechanical Drawings

